



04000A Motor Oil 10W-40 Super High Performance Diesel Truck

Document version: 2 October 2015



Art. no.	Volume	Items per unit	Items per pallet
04020A	20 L	1	30
04060A	60 L	1	12
04205A	205 L	1	2
04999A	1000 L	1	0
P04000A	bulk	1	0

Description

This high-grade semi synthetic motor oil has been specially developed for diesel engines of commercial vehicles. In addition this motor oil has been formulated to make long oil-change intervals possible and to prevent bore polishing.

Specifications

ACEA E7/E5, B3/B4
API CI-4/CH-4/CG-4/CF-4
Cummins CES 20076 / 77 / 78
Global DHD-1
Mack EO-N Premium Plus / EO-M Plus
MAN M 3275
MB-Approval 228.3
MTU Type 2
Renault RLD-2 / RLD
Volvo VDS-2 / VDS-3

Typical characteristics

Density at 15°C	0,872	kg/l
Kinematic viscosity at 40°C	86.0	mm ² /s
Kinematic viscosity at 100°C	13.1	mm ² /s
Viscosity index	153	
Dynamic viscosity at -25°C	5900	mPa·s
Flashpoint COC	243	°C
Pourpoint	-42	°C
Total Base number	16.1	mgKOH/g
Sulphated ash	1.9	mass%