



05000C3 Motor Oil 5W-40 Premium Synthetic C3

Document version: 5 October 2015



Art. no.	Volume	Items per unit	Items per pallet
05001C3	1 L	6	450
05005C3	5 L	4	112
05020C3	20 L	1	30
05060C3	60 L	1	12
05205C3	205 L	1	2
05999C3	1000 L	1	0
P05000C3	bulk	1	0

Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes Benz engines. This motor oil meets the requirements laid down by BMW Longlife-04 and Mercedes Benz Longlife 229.51. This motor oil is also suitable for Euro 4 engines according to the ACEA C3 standard. This motor oil is recommended for all petrol and diesel engines equipped with the latest exhaust gas after-treatment systems.

Specifications

ACEA A3/B4, C3
 API SN / CF
 BMW LL-04
 Ford WSS-M2C917-A
 MB-Approval 229.31 / 229.51
 Porsche A40
 Renault RN0700 / RN0710
 VW 502.00 / 505.00 / 505.01

Typical characteristics

Density at 15°C	0,852	kg/l
Kinematic viscosity at 40°C	85.0	mm ² /s
Kinematic viscosity at 100°C	14.2	mm ² /s
Viscosity index	175	
Dynamic viscosity at -30°C	5750	mPa·s
Flashpoint COC	214	°C
Pourpoint	-36	°C
Total Base number	7.6	mgKOH/g
Sulphated ash	0.8	mass%
Noack evaporation loss	8.9	mass%