

## 05000DPF Motor Oil 5W-30 Premium Synthetic C3

**DPF** 

Document version: 1 October 2015



Art. no.	Volume	ltems per unit	ltems per pallet
05001DPF	1 L	6	450
05005DPF	5 L	4	112
05020DPF	20 L	1	30
05060DPF	60 L	1	12
05205DPF	205 L	1	2
05999DPF	1000 L	1	0
P05000DPF	bulk	1	0

Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes Benz engines. This motor oil meets the requirements laid down by BMW Long Life 04 and Mercedes Benz Long Life 229.51. This motor oil is also suitable for Euro-4 engines according to the ACEA C3 standard. This motor oil is recommended for all petrol and diesel engines that are fitted with the latest exhaust gas after-treatment systems.

**Specifications** 

ACEA C3
API SN / CF
BMW LL-04
MB-Approval 229.51
VW 502.00 / 505.00

Typical characteristics	Density at 15°C	0,855	kg/l
	Kinematic viscosity at 40°C	74.3	mm <sup>2</sup> /s
	Kinematic viscosity at 100°C	12.4	mm²/s
	Viscosity index	166	
	Dynamic viscosity at -30°C	6060	mPa∙s
	Flashpoint COC	230	°C
	Pourpoint	-39	°C
	Total Base number	7,6	mgKOH/g
	Sulphated ash	0.8	mass%
	High Temperature / High Share	0	mPa∙s
	Noack evaporation loss	0	mass%