



35000A STOU 10W-40 GL-4 Multitrac Semi Synthetic

Document version: 19 October 2015



Art. no.	Volume	Items per unit	Items per pallet
35001A	1 L	6	450
35005A	5 L	4	112
35020A	20 L	1	30
35060A	60 L	1	12
35205A	205 L	1	2
35999A	1000 L	1	0
P35000A	bulk	1	0

Description

This high-grade semi synthetic STOU (Super Tractor Oil Universal) Multitrac 10W-40 multifunctional agricultural oil has been specially developed for use in diesel engines, transmissions, power take-off, wet brakes, hydraulic systems, power steering and end drive of among others tractors, combines, road and hydraulic engineering machines.

Specifications

API CE/CF-4/SF/GL-4
Caterpillar TO-2
Denison HF-0
DIN 51524 / 3 HVL
Ford M2C159B / C
John Deere J20C / J27A
Massey Ferguson M-1127 / M-1135 / M-1139 / M-1144
MB-Approval 228.1
New Holland 526C

Page 1/2

ZF TE-ML 06B / 07B

Typical characteristics

Density at 15°C	0,875	kg/l
Kinematic viscosity at 40°C	96.0	mm ² /s
Kinematic viscosity at 100°C	14.1	mm ² /s
Viscosity index	150	
Dynamic viscosity at -25°C	7000	mPa·s
Flashpoint COC	220	°C
Pourpoint	-35	°C
Total Base number	10.7	mgKOH/g