



51000C Fork Oil Medium Heavy 15W

Document version: 28 October 2015



Art. no.	Volume	Items per unit	Items per pallet
51001C	1 L	6	450
51020C	20 L	1	30
51060C	60 L	1	12
51205C	205 L	1	2
51999C	1000 L	1	0

Description

This MPM high quality 15W Fork Oil is specially developed for use in telescopic forks and shock absorbers of road/off-road motorcycles and mopeds. This fork oil is produced with high quality mineral oils with high viscosity index. The high de-aeration properties of this MPM fork oil means that there is minimum/reduced foaming in the fork legs/shock absorber bodies. This gives optimal performance and stability not only for normal day to day use, but will maintain optimal performance under extreme road/off-road conditions. MPM 15W-Fork oil offers excellent protection against component wear and seal corrosion, thus resulting in increased longevity of the components.

Note: Can also be used in shock-absorbers and telescopic forks of mountain bikes and bicycles where the manufacturer specifies a 15W oil.

Specifications

SAE 15W

Typical characteristics

Density at 15°C	0,880	kg/l
Colour	blue	
Kinematic viscosity at 40°C	46,4	mm ² /s
Kinematic viscosity at 100°C	8,3	mm ² /s
Viscosity index	155	
Flashpoint COC	210	°C
Pourpoint	-45	°C