



## 51000D Fork Oil Heavy 20W

Document version: 16 December 2015



Art. no.	Volume	Items per unit	Items per pallet
51001D	1 L	6	450
51020D	20 L	1	30
51060D	60 L	1	12
51205D	205 L	1	2
51999D	1000 L	1	0

### Description

This MPM high quality 20W Fork Oil is specially developed for use in telescopic forks and shock absorbers of road/off-road motorcycles and mopeds. This fork oil is produced with high quality mineral oils with high viscosity index. The high de-aeration properties of this MPM fork oil means that there is minimum/reduced foaming in the fork legs/shock absorber bodies. This gives optimal performance and stability not only for normal day to day use, but will maintain optimal performance under extreme road/off-road conditions. MPM 20W-Fork oil offers excellent protection against component wear and seal corrosion, thus resulting in increased longevity of the components. This high viscosity MPM 20W Fork oil, is suitable for extreme usage such as circuit, Moto-cross, and Enduro racing.

Note: Can also be used in shock-absorbers and telescopic forks of mountain bikes and bicycles where the manufacturer specifies a 20W oil.

### Specifications

SAE 20W

## Typical characteristics

Density at 15°C	0,885	kg/l
Colour	blue	
Kinematic viscosity at 40°C	62,5	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	10,4	mm <sup>2</sup> /s
Viscosity index	155	
Flashpoint COC	220	°C
Pourpoint	-45	°C