



Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue:

Revision date: 01/04/2014

:

version: 38.1

A201

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Silicon Spray Aerosol
Product code : A201
Type of product : Aerosol
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : This silicon spray is a colourless and odourless product that protects against rust, dirt and moisture, with good lubrication properties. MPM Silicon spray is very suitable as a lubricant for moving parts that come into direct contact with moisture and is very suitable as a product that protects against the freezing of among other things locks, hinges and rubber door seals.
Use of the substance/mixture : Automotive care products

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft - Nederland
T +31 (0)15 2514030 - F +31 (0)15 2514031
info@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

CLP Signal word : Danger.
Hazard statements (CLP) : H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F

P501 - Dispose of contents/container to officially registered waste disposal company

P300 - Without adequate ventilation formation of explosive mixtures may be possible

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Harmful: may cause lung damage if swallowed.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	25 - 50	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	25 - 50	Flam. Gas 1, H220 Compressed gas, H280
butane	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	2,5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	(EC no) 927-510-4 (EC index no) 01-2119475515-33-xxxx	2,5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane	(EC no) 01-2119475514-35-xxxx (EC index no) 921-024-6	2,5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation : Take victim to fresh air, in a quiet place and if necessary take medical advice.

After skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

After eye contact : In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : May form flammable/explosive vapour-air mixture. On heating/burning: release of (highly) toxic gases/vapours e.g.: carbon monoxide - carbon dioxide.

Explosion hazard : Vapours may form explosive mixtures with air. Heat from a fire could result in drum bursting.

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

- Protection during firefighting : Self-contained breathing apparatus with an air line.
- Other information : Cool containers / tanks with spray water if possible. Do not allow water used to extinguish fire to enter drains or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away. Keep away from sources of ignition - No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing and eye/face protection. Wear respiratory protection.
- Emergency procedures : Provide adequate ventilation.

6.1.2. For emergency responders

- Protective equipment : Wear respiratory protection. Wear suitable protective clothing and eye/face protection.

6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Do not flush into surface water or sewer system. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).
- Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
- Other information : Ensure adequate ventilation.

6.4. Reference to other sections

Information on disposal - see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured. Avoid contact with skin and eyes. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
- Hygiene measures : When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a well-ventilated place. Keep container tightly closed.
- Storage conditions : Protect from heat and direct sunlight.
- Prohibitions on mixed storage : Observe official regulations on storing packagings with pressurized containers.
- Storage area : Keep container tightly closed in a cool, well-ventilated place. Store according to local legislation.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
EU	IOELV TWA (mg/m³)	1430 mg/m³
EU	IOELV TWA (ppm)	600 ppm

8.2. Exposure controls

- Personal protective equipment : Gloves. Safety glasses.

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing	: Suitable material: nitrile rubber. Thickness of glove material: ≥ 0.45 mm
Hand protection	: In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves
Eye protection	: Tightly sealed safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Type AX



Other information	: When using do not eat, drink or smoke. Wash hands before breaks and at the end of work. Do not breathe vapour or spray. Avoid contact with skin and eyes. Remove/Take off immediately all contaminated clothing.
-------------------	--

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: colourless.
Odour	: Benzine.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not determined.
Freezing point	: Not determined.
Boiling point	: Not determined.
Flash point	: Not applicable as aerosol.
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 580 g/l
Solubility	: Water: not miscible Organic solvent: 93,1 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive. In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 538,7 g/l
Other properties	: Product is not explosive. Vapours may form explosive mixtures with air.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide. aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

isobutane (75-28-5)

LC50 inhalation rat (Vapours - mg/l/4h)	> 50 mg/l/4h
---	--------------

propane (74-98-6)

LC50 inhalation rat (Vapours - mg/l/4h)	20 mg/l/4h
---	------------

butane (106-97-8)

LC50 inhalation rat (Vapours - mg/l/4h)	658 mg/l/4h
---	-------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

LD50 oral rat	> 5840 mg/kg
---------------	--------------

LD50 dermal rat	> 2920 mg/kg
-----------------	--------------

LC50 inhalation rat (Vapours - mg/l/4h)	> 23,3 mg/l/4h
---	----------------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane

LD50 oral rat	> 5840 mg/kg
---------------	--------------

LD50 dermal rat	> 2920 mg/kg
-----------------	--------------

LC50 inhalation rat (Vapours - mg/l/4h)	< 25,2 mg/l/4h
---	----------------

Skin corrosion/irritation : Not classified
slightly irritant but not relevant for classification

Serious eye damage/irritation : Not classified
No irritant effect

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Silicon Spray Aerosol

Vaporizer	Aerosol
-----------	---------

Potential adverse human health effects and symptoms : Irritating. May be narcotic.

SECTION 12: Ecological information

12.1. Toxicity

General : Do not release in groundwater, surfacewater or sewerage. Danger of drinking-water pollution (ground water).

Ecology - water : Harmful to aquatic organisms.

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50 Daphnia 1	3 mg/l 48h
----------------	------------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane

EC50 Daphnia 1	3 mg/l 48h
----------------	------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of with domestic waste.
Waste disposal recommendations	: Remove to an authorized waste treatment plant.
Waste materials	: Waste disposal according to official state regulations.
European List of Waste (LoW) code	: 15 01 04 - metallic packaging 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.	: 1950
UN-No. (IMDG)	: 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Transport document description	: UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 2.1
Danger labels (UN)	: 2.1



IMDG

Transport hazard class(es) (IMDG)	: 2.1
Danger labels (IMDG)	: 2.1



14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: 5F
Limited quantities (ADR)	: 1I
Transport category (ADR)	: 2

Silicon Spray Aerosol

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Tunnel restriction code (ADR) : D

- Transport by sea

Limited quantities (IMDG) : SP277

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 538,7 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

9.1	Solubility in organic solvents	Added	
9.2	VOC content	Removed	
15.1	VOC content	Removed	

Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Compressed gas	Gases under pressure : Compressed gas
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product